



Leistung / Power	1,0 kW
Drehzahl / Tool speed	212 rpm
Betriebsart / Operating mode	S3 - 10%
Spannung / Voltage	Y 400 V / 50 Hz
Luftdruck / Air pressure	5 bar <math>p < 10 \text{ bar}</math>
Luftverbrauch / Air consumption	3 - 6 l/s
Volumen Spänebehälter / Capacity chip tank	2,5 l
Masse / Weight	ca. 23 kg

<p>Lutz Precision</p> <p><small>This document contains confidential and proprietary information, which may not be duplicated, published, disseminated or disclosed to unintended third party recipients (or just "third parties") or used for any purpose, without written permission from Lutz Precision. If you are an unintended recipient of this proprietary information or are unwilling to accept the above restrictions, please immediately return this document to LUTZ - Precision s.r.o. Bratislava, Slovakia</small></p>	Masse / Weight [kg]: 0	Oberfläche / Surface:	Wärmebeh./Heat-treatm.:
	Toleranzen / Tolerances DIN ISO 2768-m	Maßstab / Scale: 1:6	Werkstoffnr. / Material No.:
	Datum/Date 21.11.2008	Name jrybansky	Rohm. / Feedstock: 1
	Gez./Drwn. Sepr./Chk'd Freig./Appr'd MFG:	Benennung / Title: Elektrodenkappenfräser E2A Electrode tip dresser E2A	
<p>Lutz Precision</p> <p><small>Property of LUTZ - Precision s.r.o. Bratislava, Slovakia www.Lutz-Precision.com</small></p>		Zeichnungsnummer / Drawing No.:	A3
Pos. Änderungen / Modification Date Name		Ursprung/Source:	Version/Revision: 000
		0.21.00.24A	1 2